



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 1/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : AOR Black Rust Inhibitor - Quart and Gallon
Supplier Product Numbers : AOR-32 & AOR-128

1.2 Other Means of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Rust Inhibiting Primer
Restrictions on Use : None Identified

1.4 Supplier Details

	Manufacturer Details	Supplier Details
Company Name		AGS Company Automotive Solutions LLC
Address		PO Box 729, Muskegon, MI 49443 - United States
Phone Number		800-253-0403
Fax Number		
Email		customerservice@agscompany.com
Website		www.agscompany.com

1.5 24 hr Emergency Phone Number

Emergency Number : 1-800-255-3924
CHEM-TEL - 24 Hour Emergency Contact

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Skin Irrit. 2	H315	Health Hazards	Skin corrosion/irritation Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Skin Sens. 1	H317	Health Hazards	Skin sensitization, Category 1
Carc. 1a	H350	Health Hazards	Carcinogenicity Category 1A
Repr. 2	H361	Health Hazards	Reproductive toxicity Category 2
Stot Se 3	H335	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Respiratory tract irritation
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Narcosis
Aquatic Acute 2	H401	Environmental Hazards	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	H411	Environmental Hazards	Hazardous to the aquatic environment - Chronic Hazard Category 2

2.2 Label Elements

Hazard Pictograms



GHS02



GHS07



GHS08



GHS09

Signal Word

Danger

Hazard Statements

H225 : Highly flammable liquid and vapour
H315 : Causes skin irritation
H317 : May cause an allergic skin reaction
H319 : Causes serious eye irritation



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 2/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	H335	: May cause respiratory irritation
	H336	: May cause drowsiness or dizziness
	H350	: May cause cancer
	H361	: Suspected of damaging fertility or the unborn child
	H401	: Toxic to aquatic life
	H411	: Toxic to aquatic life with long lasting effects
Precautionary Statements	P202	: Do not handle until all safety precautions have been read and understood.
	P210	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233	: Keep container tightly closed.
	P240	: Ground/Bond container and receiving equipment.
	P241	: Use explosion-proof electrical/ventilating/lighting equipment.
	P242	: Use only non-sparking tools.
	P243	: Take precautionary measures against static discharge.
	P261	: Avoid breathing fumes .
	P264	: Wash hands thoroughly after handling.
	P271	: Use only outdoors or in a well-ventilated area.
	P272	: Contaminated work clothing must not be allowed out of the workplace.
	P273	: Avoid release to the environment.
	P280	: Wear protective gloves and eye protection.
	P302+P352	: If on skin: Wash with plenty of water.
	P303+P361+P353	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+P340	: If inhaled: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P308+P313	: If exposed or concerned: Get medical advice/attention.
	P312	: Call physician if you feel unwell.
	P333+P313	: If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	: If eye irritation persists: Get medical advice/attention.	
P362+P364	: Take off contaminated clothing and wash it before reuse.	
P370+P378	: In case of fire: Use water, CO2, dry chemical, universal aqueous or film forming foam to extinguish.	
P391	: Collect spillage.	
P403+P233	: Store in a well-ventilated place. Keep container tightly closed.	
P235	: Keep cool.	
P405	: Store locked up.	
P501	: Dispose of contents/container to applicable regulations.	

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

20.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
33.99% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
42.24% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 3/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substance name	CAS Number	% wt*	Classification
4-Chlorobenzotrifluoride	98-56-6	10 - 30	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Acetone	67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Barium Sulfate	7727-43-7	10 - 30	Aquatic Acute 3, H402
Methyl N-Propyl Ketone	107-87-9	1 - 5	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
N-Butyl Acetate	123-86-4	1 - 5	Flam. Liq. 2, H225 STOT SE 3, H336 Aquatic Acute 3, H402
Carbon Black	1333-86-4	1 - 5	Carc. 1A, H350
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	Flam. Liq. 4, H227 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
Zirconium 2-Ethylhexanoate	22464-99-9	0.1 - 1	Repr. 2, H361

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

General Measures	: If exposed or concerned: Get medical advice/attention.
Inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
Skin Contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Call a poison center or a doctor if you feel unwell.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Muscle Ache, Dermatitis, Central Nervous System Depression, Respiratory Irritation, Skin Irritation, Headache, Dizziness, Nausea, Narcosis, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Chills, Fever, Dry Throat, Cough, Blurred Vision, Malaise, Chest Tightness, Mucous Membrane.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Central Nervous System, Eyes, Respiratory System, Skin.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 4/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media : Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media : Water jet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products : Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting : CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions : Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

Environmental Precautions : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures : Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
Cleanup Procedures : Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information : The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
Prohibited Materials : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

General Handling Precautions : KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Application using Flammable and Combustible Materials is recommended.
Hygiene Recommendations : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

Storage Requirements : Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.
Incompatibilities : Segregate storage away from materials indicated in Section 10.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 5/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)

ACGIH	ACGIH TWA (mg/m ³)	250 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m ³)	1200 mg/m ³
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m ³)	1780 mg/m ³
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

N-Butyl Acetate (123-86-4)

ACGIH	ACGIH TWA (mg/m ³)	150 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	200 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
NIOSH	US IDLH (ppm)	1700 ppm
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
NIOSH	NIOSH REL (STEL) (ppm)	200 ppm
California	California PEL (TWA) (mg/m ³)	710 mg/m ³
California	California PEL (TWA) (ppm)	150 ppm
California	California PEL (STEL) (mg/m ³)	950 mg/m ³
California	California PEL (STEL) (ppm)	200 ppm

Methyl N-Propyl Ketone (107-87-9)

ACGIH	ACGIH TWA (mg/m ³)	200 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	700 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	US IDLH (ppm)	1500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm

Carbon Black (1333-86-4)

ACGIH	ACGIH TWA (ppm)	3 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
NIOSH	US IDLH (mg/m ³)	1750 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³
California	California PEL (TWA) (mg/m ³)	3.5 mg/m ³

Barium Sulfate (7727-43-7)

ACGIH	ACGIH TWA (ppm)	5 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)

Methyl Ethyl Ketoxime (96-29-7)

AIHA	WEEL TWA (ppm)	10 ppm
------	----------------	--------

8.2 Exposure Controls

Engineering Measures

: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

Personal Protective Equipment

Eye / Face Protection

: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

Hand Protection

: Chemical-resistant gloves, tested according to ASTM F903 - 17.

Remarks

: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 6/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and Body Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
Respiratory Protection	: Respiratory protection is not anticipated to be needed.
Compliance	: If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.
Other Protective Equipment	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.
Environmental Exposure Controls	: Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 56.00 °C	Melting / Freezing Point	> -108.00 °C
Flash Point, Liquid	> -18.00 °C		
Explosive Limits	LEL: 0.90 UEL: 24.60 vol %	Autoignition Temperature, Liquid	> 140.00 °C
Flammability	Highly Flammable Liquid	Density	1.251 g/cm ³
Molecular Weight	Not Available	Weight	10.440 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	Not Available
Appearance / Color	Black	Water Solubility	Not Available
Odor	Paint-like	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	50.38 % wt	VOC Regulatory	190.29 g/L (1.59 lbs/gal)
Percent VOC	8.90 % wt	VOC Actual	111.30 g/L (0.93 lbs/gal)
Percent HAP	0.58 % wt	HAP Content	7.26 g/L (0.06 lbs/gal)
Global Warming Potential	0.10 GWP	Maximum Incremental Reactivity	0.3520 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Hot Surfaces, Heat, Flames, Sparks.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Bromine Pentafluoride, Strong Acids, Aluminum, Potassium t-Butoxide, Bases, Calcium Hypochlorite, Hydrogen Peroxide, Magnesium, Perchloric Acid, Organic Peroxides.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes, Formaldehyde, Methanol, Acetic Acid.



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 7/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (GESTIS Substance Database)

Zirconium 2-Ethylhexanoate (CAS: 22464-99-9 / EC: 245-018-1)

LD50 Oral (Rat)	> 5000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 5000 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 8800 mg/m ³ (RTECS)

4-Chlorobenzotrifluoride (CAS: 98-56-6 / EC: 202-681-1)

LD50 Oral (Rat)	13000 mg/kg (Hazardous Substances Data Bank)
LD50 Dermal (Rabbit)	3300 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	33 mg/l/4h (Hazardous Substances Data Bank)

N-Butyl Acetate (CAS: 123-86-4 / EC: 204-658-1)

LD50 Oral (Rat)	13100 mg/kg (IUCLID)
LD50 Dermal (Rabbit)	> 14100 mg/kg (IUCLID)
LC50 Inhalation (Rat)	> 21 mg/l/4h (IUCLID)
LC50 Inhalation (Rat)	390 ppm/4h (RTECS)

Methyl N-Propyl Ketone (CAS: 107-87-9 / EC: 203-528-1)

LD50 Oral (Rat)	3020 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	6500 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 25.5 mg/l/4h (Sigma-Aldrich)
LC50 Inhalation (Rat)	2000 ppm/4h (ChemInfo)

Carbon Black (CAS: 1333-86-4 / EC: 215-609-9)

LD50 Oral (Rat)	> 15400 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 3000 mg/kg (RTECS)
LC50 Inhalation (Rat)	27 mg/l/4h (ChemInfo)

Barium Sulfate (CAS: 7727-43-7 / EC: 231-784-4)

LD50 Oral (Rat)	> 5000 mg/kg (Lit.)
-----------------	---------------------

Methyl Ethyl Ketoxime (CAS: 96-29-7 / EC: 202-496-6)

LD50 Oral (Rat)	> 930 mg/kg (RTECS)
LD50 Dermal (Rat)	> 2000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 1000 mg/kg body weight (RTECS)
LC50 Inhalation (Rat)	20 mg/l/4h (Lit.)

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.
Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure	: See Section 4.2
Skin Corrosion/Irritation	: Causes skin irritation.
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: May cause an allergic skin reaction.
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
STOT-Single Exposure	: May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-Repeated Exposure	: Not classified
Aspiration Hazard	: Not classified
Carcinogen Data	: The following ingredients are listed as known or suspected carcinogens:



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 8/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Black (CAS: 1333-86-4 / EC: 215-609-9)

ACGIH Category

A3 - Confirmed animal carcinogen with unknown relevance to humans

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

Acetone (67-64-1)

LC50 Fish	5540 mg/l Rainbow Trout - 96hr
LC50 Fish	8300 mg/l Bluegill Sunfish - 96h
EC50 Daphnia	8800 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 90% / 28 days.
Biochemical Oxygen Demand	1.43 g O ₂ /g substance
Chemical Oxygen Demand	1.92 g O ₂ /g substance
Theoretical Oxygen Demand	2.2 g O ₂ /g substance
BCF Fish	0.69
BCF Other Aquatic Organisms	3
Log Pow	-0.24

4-Chlorobenzotrifluoride (98-56-6)

LC50 Fish	5.6 mg/l Bluegill Sunfish - 96h
LC50 Fish	13.5 mg/l Rainbow Trout - 24hr
Persistence and Degradability	Biodegradability in water: no data available.
Log Pow	3.6
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).

n-Butyl Acetate (123-86-4)

LC50 Fish	62 mg/l Golden Orfe - 96hr
LC50 Fish	18 mg/l Fathead Minnow - 96h
EC50 Daphnia	72.8 mg/l Water Flea - 24hr
EC50 Other Aquatic Organisms	675 mg/l Green Algae - 72hr
EC50 Other Aquatic Organisms	959 mg/l Bacteria - 18hr
Persistence and Degradability	Biodegradability 88% / 28 days.
Biochemical Oxygen Demand	520 mg/g
Chemical Oxygen Demand	2320 mg/g
Theoretical Oxygen Demand	2207 mg/g
Log Pow	1.804
Log Koc	2.35

Methyl n-Propyl Ketone (107-87-9)

LC50 Fish	1240 mg/l Fathead Minnow - 96h
EC50 Daphnia	> 110 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	> 150 mg/l Green Algae - 72hr
Persistence and Degradability	Biodegradability 70% / 28 days.
Log Pow	0.857 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).
Log Koc	1.87 (log Koc, Estimated value)

Carbon Black (1333-86-4)

LC50 Fish	1000 mg/l Zebra Fish - 96hr
EC50 Daphnia	5600 mg/l Water Flea - 24hr
EC50 Other Aquatic Organisms	10000 mg/l Green Algae - 72hr
Chemical Oxygen Demand	Not applicable
Theoretical Oxygen Demand	Not applicable
Log Pow	1.09
Bioaccumulative Potential	Not bioaccumulative.

Barium Sulfate (7727-43-7)

LC50 Fish	> 174 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia	32 mg/l Water Flea - 48hr



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 9/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Barium Sulfate (7727-43-7)

Chemical Oxygen Demand	Not applicable
Theoretical Oxygen Demand	Not applicable
BCF Fish	1.2 - 74.4 l/kg (Lepomis macrochirus, Fresh water, Experimental value)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).

Methyl Ethyl Ketoxime (96-29-7)

LC50 Fish	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia	201 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
BCF Fish	0.5 - 5.8 (OECD 305: Bioconcentration: Flow-Through Fish Test, 42 day(s), Cyprinus carpio, Fresh water, Experimental value, GLP)
Log Pow	0.63 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.55 (log Koc, SRC PCKOCWIN v2.0, QSAR)

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.
Incineration Precautions	: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1263	UN1263	UN1263

14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity

14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 3	3	3
Labels	: None	3 - Flammable liquid	None



Limited Quantity	: Yes	Yes	Yes
EmS Code	: Not Applicable	Not Applicable	F-E, S-E

14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Packing Group	: II	II	II



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 10/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5 Environmental Hazards

Marine Pollutant : DOT (USA) No IATA (AIR) No IMDG (OCEAN) No

14.6 Special Precautions

Precautions : None Identified

14.7 Transport in Bulk

Remarks : Not applicable for product as supplied

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313 : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Xylene	CAS-No. 1330-20-7	0.1 - 1%
Ethyl Benzene	CAS-No. 100-41-4	0.01 - 0.1%
Secondary Butyl Alcohol	CAS-No. 78-92-2	0.001 - 0.01%

TSCA Section 12(b) : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

CERCLA Reportable Quantity : Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
Xylene	CAS-No. 1330-20-7	100 lb
Ethyl Benzene	CAS-No. 100-41-4	1000 lb
Methyl Ethyl Ketone	CAS-No. 78-93-3	5000 lb

15.2 State Regulations

California Proposition 65 : This product contains chemicals known to the State of California to cause cancer.

Quartz (14808-60-7)	Cancer	Yes	0.0815 %
4-Chlorobenzotrifluoride (98-56-6)	Cancer	Yes	22.17 %
Ethyl Benzene (100-41-4)	Cancer	Yes	0.0855 %
Carbon Black (1333-86-4)	Cancer	Yes	2.25 %
Ethyl Benzene (100-41-4)	No significance risk level (NSRL)	54	

State Right-to-Know Lists : The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Epoxidized Soybean Oil (8013-07-8)	U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List
Xylene (1330-20-7)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Ethyl Benzene (100-41-4)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Methyl n-Propyl Ketone (107-87-9)	U.S. - New Jersey - Right to Know Hazardous Substance List
Carbon Black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List
Zinc Oxide (1314-13-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
Barium Sulfate (7727-43-7)	U.S. - New Jersey - Right to Know Hazardous Substance List
Precipitated Silica (112926-00-8)	U.S. - New Jersey - Right to Know Hazardous Substance List



SAFETY DATA SHEET

Part No. AOR-32 (Liquid) & AOR-128 (Liquid)

Print Date: 24/01/2020
Revision Date: 1/24/2020
Supersedes Date: 1/24/2020
Issue Date: 1/24/2020
Version: 1.0 (EN)-US
Page: 11/11

AOR Black Rust Inhibitor

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Butoxyethanol (111-76-2)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Secondary Butyl Alcohol (78-92-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
Methyl Ethyl Ketone (78-93-3)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 - OTHER INFORMATION

Indication of changes :

Section	Changed item	Change
1	Created Safety Data Sheet - Revision 1	Added

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.